



## TV80 0035

**Product code:** TV80 0035

**Manufacturer:** Twiga

The HDMI standard allows you to use an HDMI cable to carry a basic local HD signal to a Standard monitor.

Built around a powerful FPGA signal processing component, the interface card can be used beyond a simple transmission system to completely manage an industrial vision system.

### FEATURES:

- HDMI Digital and Analog HD video output up to 1080p60
- Automatic SONY camera recognition
- Video format selection with micro switches 6 x keyswitch channels for zoom & memory control
- TTL or RS232 SONY VISCA dialog level
- 6 to 12 VDC protected power supply for interface and camera

### APPLICATIONS:

- Broadcasting
- Low vision
- Industrial
- Medical applications



**Tecnosens S.p.A.**  
Via Vergnano,16 25125  
Brescia (BS) Italia

Tel: (+39) 030 3534144  
Fax: (+39) 030 3530815  
info@tecnosens.it  
PEC: tecnosens@legalmail.it

- Security

<b>Power Supply</b>	6 a 12 VDC, 6 W (camera included) 5V for SE600
<b>Connector</b>	HDMI
<b>Dimension (mm)</b>	48 (H) x 45 (L) x 20 (P)
<b>Output protocol</b>	HDMI
<b>Working temperature</b>	From 0°C to 60°C
<b>Analogue Video Output</b>	Y, Pb, Pr, 75 ohms, 1V .-(not with SE 600)