



## 3SFF

**Product code:** 3SFF

**Manufacturer:** City Technology

### MEASUREMENT

**Operating Principle:** 3-electrode electrochemical

**Nominal Range:** 0-2000 ppm SO<sub>2</sub>

**Maximum Overload:** 5000 ppm SO<sub>2</sub>

**Filter:** To remove H<sub>2</sub>S & HCl

**Sensitivity:** 0.10 ± 0.02 µA/ppm

**Response Time (T<sub>90</sub>):** <35 Seconds

**Baseline Offset (clean air):** ±2 ppm equivalent

**Zero Shift (+20°C to +40°C):** <5 ppm equivalent

**Resolution:** 1 ppm (electronics dependant)

**Repeatability:** 1% of signal

**Output Linearity:** Linear

### ELECTRICAL

**Recommended Load Resistor:** 10 Ω

**Bias Voltage:** Not Required

### MECHANICAL

**Weight:** 22 g

**Housing Material:** Glass filled polypropylene

**Orientation:** Any

### ENVIRONMENTAL

**Operating Temperature Range:** -20°C to +50°C

**Recommended Storage Temp:** 0°C to 20°C

**Operating Pressure Range:** Atmospheric ± 10%

**Pressure Coefficient:** 0.004 % signal/mBar

**Operating Humidity Range:** 15 - 90% RH non-condensing

### LIFETIME

**Long Term Sensitivity Drift:** <2% signal loss / month

**Expected Operating Life:** Two years in air

**Storage Life:** 6 months in CTL container



**Tecnosens S.p.A.**  
Via Vergnano,16 25125  
Brescia (BS) Italia  
  
Tel: (+39) 030 3534144  
Fax: (+39) 030 3530815  
info@tecnosens.it  
PEC: tecnosens@legalmail.it

---

<b>Life expectancy</b>	> 24 months
<b>Measurement range</b>	0-2000 ppm
<b>Target Gas</b>	Sulfur Dioxide
<b>Response Time</b>	< 35 seconds (T90)
<b>Output</b>	100 ± 20 nA/ppm