



3EF

Product code: 3EF

Manufacturer: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-1000 ppm CO

Maximum Overload: 2000 ppm CO

Filter: To remove SOx/NOx & H2S

Sensitivity: $0.10 \pm 0.02 \mu\text{A}/\text{ppm}$

Resolution: 0.5 ppm CO

Response Time (T90): <30 seconds

Baseline Offset (clean air): -1 to +3 ppm equivalent

Zero Shift (+20°C to +40°C): <9 ppm equivalent

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: Not required

MECHANICAL

Weight: 22 g

Housing Material: 20% Glass Filled Polypropylene

Orientation: Any

ENVIRONMENTAL

Typical Applications: Fixed Life Safety

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric $\pm 10\%$

Pressure Coefficient: $0.020 \pm 0.008 \%$ signal/mBar

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: <5% signal loss/year

Expected Operating Life: Three years in air

Storage Life: 6 months in CTL container



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Life expectancy	> 3 years
Measurement range	0-1000 ppm
Target Gas	Carbon Monoxide
Response Time	< 30 seconds (T90)
Output	100 ± 20 nA/ppm