



5SF

Product code: 5SF

Manufacturer: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-2000 ppm SO₂

Maximum Overload: 5000 ppm SO₂

Filter: None

Sensitivity: 0.10 ± 0.02 µA/ppm

Resolution: 1 ppm

Response Time (T90): <30 seconds

Baseline Offset (clean air): 0 - 2 ppm equivalent

Maximum Zero Shift (+20°C to +40°C): 5 ppm equivalent

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: Not Required

MECHANICAL

Weight: 10 g nominal

Orientation: Any

ENVIRONMENTAL

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric ± 10%

Pressure Coefficient: 0.004% signal / mbar

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: < 2% signal loss/year

Expected Operating Life: Two years in air

Storage Life: 6 months in CTL container



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Life expectancy	> 24 months
Measurement range	0-2000 ppm
Target Gas	Sulfur Dioxide
Response Time	< 30 seconds (T90)
Output	100 ± 20 nA/ppm