

No image
available

7ETO

Product code: 7ETO

Manufacturer: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-20 ppm C₂H₄O

Maximum Overload: 100 ppm C₂H₄O

Filter: None

Sensitivity: $2.25 \pm 0.65 \mu\text{A/ppm}$

Response Time (T₉₀): <140 Seconds

Baseline Offset (clean air): 0 to +1 ppm C₂H₄O equivalent

Zero Shift (+20°C to +40°C): < 2 ppm C₂H₄O equivalent

Resolution: 0.1 ppm (when used with recommended electronics)

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: +300 mV

MECHANICAL

Weight: 17 g nominal

Housing Material:

- Cap: Polycarbonate
- Body: ABS

Orientation: Any

ENVIRONMENTAL

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric \pm 10%

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Long Term Sensitivity Drift: < 5% signal loss/year
Expected Operating Life: Three years in air
Storage Life: 6 months in CTL container

Life expectancy	> 24 months
Measurement range	0-20 ppm
Target Gas	Ethylene Oxide
Response Time	< 140 seconds (T90)
Output	2.25 ± 0.65 µA/ppm