



GUVx-S1xSS2

Product code: GUVx-S1xSS2

Manufacturer: Genicom Co., Ltd.

Description: It inform the UV power of UV source through the LCD using UV Sensor. You can choose the sensor part by your application.

Costitution: Display, Adapter, Probe (Sensor + Connection line), Output Line.

Application by UV Probe

- Outdoor UV Index: H3

Features

- Fixing method: 2 Fixing Hole
- Power: AC 100 ~ 240V (50/60Hz)
- Display: Absolute Optical Power (Max. 100 mW/cm²)
- Output:
 - 2 Relay (NO&COM, NC&COM)
 - 4-20 mA Current (Option)
 - RS485 Communication (Option)

Specifications

- Size : 96 mm X 48 mm X 108 mm
- Operating Temperature:
 - Display : 0 ~ 50 C
 - UV Sensor Probe: -30 ~ 85 C
 - Cable length: 5m (Standard)
- Detection Range:
 - UVV : 230 ~ 395 nm
 - UVA : 220 ~ 370 nm
 - UVB : 220 ~ 320 nm
 - UVC : 220 ~ 280 nm

Power Supply	AC 100 ~ 240V 50/60 Hz
Dimension	96 x 48 x 108



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Wavelength	230-395 nm 220-320 nm 220-280 nm 220-370 nm
Output	RS485 4-20 mA Relay