



## GUVx-T1xGS4

**Product code:** GUVx-T1xGS4

**Manufacturer:** Genicom Co., Ltd.

**Description:** UV Radiometer 4 is 3 Channel indicator. There are 3 type display, and 2 type output (Relay and 4-20 mA). 3 type display is the Relative Power (%), Accumulative Time (Hours), and Absolute Power (mW/cm<sup>2</sup>).

**Constitution:** Display, Sensor Probe 3 ea, Connection Cable 3 ea (5 m).

### Application by UV Probe

- Air/Curing: LA2, LA5, LA6
- Water treatment: LW5, LW10

### Features

- Fixing method: Panel Insertion
- Power: AC 200 ~ 240V (50/60Hz)
- Display:
  - Relative Power (%)
  - Accumulative Time (Hours)
  - Absolute Optical Power (mW/cm<sup>2</sup>)
  - 3 Color LED (Green, Yellow, Red)
- Output:
  - 4-20 mA Current, 5 V (Depends on Absolute Optical Power)
  - Relay

### Specifications

- Size : 96 mm X 96 mm X 111 mm
- Operating Temperature:
  - Display : 0 ~ 50 C
  - UV Sensor Probe: -30 ~ 85 C
  - Cable length: 5m (Standard)
- Detection Range:
  - UVV : 230 ~ 395 nm
  - UVA : 220 ~ 370 nm
  - UVB : 220 ~ 320 nm
  - UVC : 220 ~ 280 nm



**Tecnosens S.p.A.**  
Via Vergnano,16 25125  
Brescia (BS) Italia  
  
Tel: (+39) 030 3534144  
Fax: (+39) 030 3530815  
info@tecnosens.it  
PEC: tecnosens@legalmail.it

---

<b>Power Supply</b>	AC 200 ~ 240V 50/60 Hz
<b>Dimension</b>	96 x 96 x 111
<b>Wavelength</b>	230-395 nm 220-370 nm 220-280 nm 220-320 nm
<b>Output</b>	4-20 mA Relay