



GUVx-T1xGS6

Product code: GUVx-T1xGS6

Manufacturer: Genicom Co., Ltd.

Description: UV Radiometer 6 have 2 type display (Relative Power and Accumulative Time), and relay output, Simple to handle.

Application by UV Probe

- Air/Curing: LA2
- Water treatment: LW9, LW10

Features

- Fixing method: Panel Insertion
- Power: AC 85 ~ 265V (50/60Hz)
- Display:
 - Relative Power (unit : %)
 - Accumulative Time (unit : Hrs)
- Output:
 - Relay (NO&COM, 250VAC 3A/30VDC 3A)
 - 4-20 mA Current

Specifications

- Size: 48 mm X 48 mm X 107 mm
- Operating Temperature:
 - Display: 0 ~ 50 C
 - UV Sensor Probe: -30 ~ 85 C
 - Probe cable length: 5 m (standard)
- Detection Range:
 - UVV : 230 ~ 395 nm
 - UVB : 220 ~ 320 nm
 - UVC : 220 ~ 280 nm

Power Supply	AC 85 ~ 265V 50/60 Hz
Dimension	48 x 48 x 107
Wavelength	220-280 nm 220-320 nm 230-395 nm



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Output

4-20 mA
Relay