

## T-200

**Product code:** T-200

**Manufacturer:** ELT Sensor



T-200 Series sensors can be located outside the building as well as inside due to their robustness, consistent stability and Temperature change Effect Compensation.

Accuracy of  $\pm 300\text{ppm} \pm 3\%$  of reading available only for measurement ranges of 0.04-2%, 0.04-3%, 0.04-5% and 0.04-10%.

'G' version available for humidity resistance up to 99% RH for Application of Agricultural GreenHouse, Stock Raising, etc.

'L' version available to add the sleep mode for low power consumption.

<b>Accuracy</b>	$\pm 50\text{ppm} \pm 3\%$ of reading $\pm 300\text{ppm} \pm 3\%$ of reading
<b>Power Supply</b>	5.0 Vdc
<b>Dimension</b>	19.4 x 30 x10.3 mm
<b>Measurement range</b>	400-2000 ppm 400-3000 ppm 400-5000 ppm 400-10000 ppm 0.04-2% 0.04-3% 0.04-5% 0.04-10%
<b>Humidity range</b>	0-95% RH 0-99% RH
<b>Target Gas</b>	Anidride Carbonica
<b>Operating temperature</b>	-20°C / +60°C



**Tecnosens S.p.A.**  
Via Vergnano,16 25125  
Brescia (BS) Italia

Tel: (+39) 030 3534144  
Fax: (+39) 030 3530815  
info@tecnosens.it  
PEC: tecnosens@legalmail.it

---

**Output**

I2C  
UART  
Analogica (0.5V - 4.5V)  
PWM