



P-ROAD

Product code: P-ROAD

ANPR camera with integrated OCR, max speed 50Km/h, gate width 4mt (1 lane)

Global shutter 1.6MP image sensor

Integrated IR illuminator with stroboscopic multi-exposure

Environmental context camera (optional)

Working distance 4 - 30 mt

ROI, vehicles classification, direction and speed, local plate lists with configurable events

Options available: environment camera, motorized varifocal lens, 4G connection, local storage, sensors, PoE, wiegand, brand and model

2 digital inputs and 4 relay output

Backup system for local events

Data transmission with encrypted protocol, sFTP, FTP, HTTP, Ethernet interface 10/100Mbps.

D3NS Cloud monitoring

Web page configuration

IP67 vandal-proof metallic case

12Vdc power supply

Warranty 24 months

Maximum gate width

4 mt



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

OCR optics	Fixed
OCR resolution	1.6 MP
Sensors	None
Working distance (rear plate)	4-30 mt
Supply voltage	12Vdc
Maximum vehicle speed	50 km/h