



T3SH

Codice prodotto: T3SH

Produttore: City Technology

Sensor Type Used: 3SH

Filter: None

Output: 4-20 mA d.c.

Response Time (T90): <15 Seconds at 20°C

Resolution: 0.1 ppm

Zero Shift (-20°C to +40°C): <0.1 ppm equivalent

Repeatability: 2% of signal

Linearity: Linear

Power Supply Required: 10 - 35 VDC single-ended

Output Impedance: 4 MΩ

Calibration: Via built-in span and zero potentiometers

Mounting: Via mounting nose supplied

Weight: 58 g including mounting accessory

Position Sensitivity: None

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Temperature Compensation: None

Operating Pressure Range: Atmospheric ± 10%

Pressure Coefficient: No data

Operating Humidity Range: 15 - 90% RH non-condensing

Long Term Sensitivity Drift: <2% signal loss/month

Expected Operating Life: Two years in air

Storage Life: 6 months in CTL container

Standard Warranty: 12 months from date of despatch

Life expectancy

> 24 mesi

Target Gas

Anidride Solforosa



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Tempo di Risposta	< 15 secondi (T90)
--------------------------	--------------------

Uscita	4-20 mA
---------------	---------