



## 3H

**Codice prodotto:** 3H

**Produttore:** City Technology

### MEASUREMENT

**Operating Principle:** 3-electrode electrochemical

**Measurement Range:** 0-200 ppm H<sub>2</sub>S

**Maximum Overload:** 1000 ppm H<sub>2</sub>S

**Filter:** None

**Sensitivity:**  $0.37 \pm 0.07 \mu\text{A/ppm}$

**Response Time (T<sub>90</sub>):** <35 Seconds

**Baseline Offset (clean air):** -0.6 to +1.9 ppm H<sub>2</sub>S equivalent

**Maximum Zero Shift (+20°C to +40°C):** 2 ppm H<sub>2</sub>S equivalent

**Resolution:** 0.25 ppm (when used with recommended electronics)

**Repeatability:** 1% of signal

**Linearity:** Linear

### ELECTRICAL

**Recommended Load Resistor:** 10 Ω

**Bias Voltage:** Not required

### MECHANICAL

**Weight:** 22 g

**Housing Material:** Gap and BodyGlass Filled Polypropylene

**Orientation:** Any

### ENVIRONMENTAL

**Operating Temperature Range:** -40°C to +50°C

**Recommended Storage Temp:** 0°C to 20°C

**Operating Pressure Range:** Atmospheric  $\pm 10\%$

**Pressure Coefficient:**  $0.008 \pm 0.002 \%$  signal/mBar

**Operating Humidity Range:** 15 - 90% RH non-condensing

### LIFETIME

**Long Term Sensitivity Drift:** <2% signal loss/year

**Expected Operating Life:** Two years in air

---

**Storage Life:** 6 months in CTL container

<b>Life expectancy</b>	> 24 mesi
<b>Range di misura</b>	0-200 ppm
<b>Target Gas</b>	Acido Solfidrico
<b>Tempo di Risposta</b>	< 35 secondi (T90)
<b>Uscita</b>	370 ± 70 nA/ppm