



3H

Codice prodotto: 3H

Produttore: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-200 ppm H₂S

Maximum Overload: 1000 ppm H₂S

Filter: None

Sensitivity: $0.37 \pm 0.07 \mu\text{A/ppm}$

Response Time (T₉₀): <35 Seconds

Baseline Offset (clean air): -0.6 to +1.9 ppm H₂S equivalent

Maximum Zero Shift (+20°C to +40°C): 2 ppm H₂S equivalent

Resolution: 0.25 ppm (when used with recommended electronics)

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: Not required

MECHANICAL

Weight: 22 g

Housing Material: Gap and BodyGlass Filled Polypropylene

Orientation: Any

ENVIRONMENTAL

Operating Temperature Range: -40°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric \pm 10%

Pressure Coefficient: 0.008 ± 0.002 % signal/mBar

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: <2% signal loss/year

Expected Operating Life: Two years in air



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Storage Life: 6 months in CTL container

Life expectancy	> 24 mesi
Range di misura	0-200 ppm
Target Gas	Acido Solfidrico
Tempo di Risposta	< 35 secondi (T90)
Uscita	370 ± 70 nA/ppm