



A3EF

Codice prodotto: A3EF

Produttore: City Technology

MEASUREMENT

Operating Principle: 4-electrode electrochemical

Measurement Range: 0-2000 ppm CO

Maximum Overload: 4000 ppm CO

Filter: To remove acid gases

Sensitivity: $0.075 \pm 0.025 \mu\text{A/ppm}$

Resolution (when using recommended circuitry): 1 ppm

Response Time (T90): <38 seconds

Baseline Offset (clean air): -2 to +17 ppm equivalent

Repeatability: <1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: 0 or +250 mV

MECHANICAL

Weight: 25 g

Housing Material: Polycarbonate

Orientation: Any

ENVIRONMENTAL

Typical Applications: Ambient Environmental Monitoring

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric \pm 10%

Pressure Coefficient: 0.02% signal/mBar

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: <2% signal loss/year

Expected Operating Life: Two years in air



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Storage Life: 6 months in CTL container

Life expectancy	> 24 mesi
Range di misura	0-2000 ppm
Target Gas	Monossido di Carbonio
Tempo di Risposta	< 38 secondi (T90)
Uscita	75 ± 25 nA/ppm