



3ETO

Codice prodotto: 3ETO

Produttore: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-20 ppm C₂H₄O

Maximum Overload: 100 ppm C₂H₄O

Filter: None

Sensitivity: 2.75 ± 0.5 mA/ppm

Resolution: 0.1 ppm

Response Time (T₉₀): < 140 seconds

Baseline Offset (clean air): 0 to +1 ppm equivalent

Zero Shift (+20°C to +40°C): 2 ppm equivalent

Repeatability: 1% of signal

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: +300 mV

MECHANICAL

Weight: 22 g

Orientation: Any

ENVIRONMENTAL

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric ± 10%

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: <5% signal loss/year

Expected Operating Life: Two years in air

Storage Life: 6 months in CTL container

Life expectancy

> 24 mesi



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Range di misura	0-20 ppm
Target Gas	Ossido di Etilene
Tempo di Risposta	< 140 secondi (T90)
Uscita	2.75 ± 0.5 μ A/ppm