



50xLL

Codice prodotto: 50xLL

Produttore: City Technology

MEASUREMENT

Technology: Electrochemical

Measurement Range: 0-25% vol. O₂

Maximum Overload: 30% vol. O₂

Output Signal: 80 - 130 mA in Air

T90 Response Time: <15 Seconds

T97 Response Time: <35 Seconds

Zero Current (Offset) (after 3 minute N₂): <0.3% vol. O₂

Warm-Up Time: Refer to Characterisation Note

Linearity: $S = K \log_e 1 / (1-C)$

ELECTRICAL

Power Rating at 20.9% O₂: 0.5 mW

Bias Voltage: -600 ± 10 mV

MECHANICAL

Casing Material: ABS/NORYL

Weight: 14 ± 0.2 g

Orientation Sensitivity: <0.2% vol. O₂ equivalent

ENVIRONMENTAL

Operating Temperature Range: -40°C to +60°C

Recommended Storage Temp: 0°C to 20°C in original packaging

Thermal Transient (Temp. plunge +22°C to -20°C): <23.5% vol. O₂

Operating Pressure Range: Atmospheric ± 20%

Pressure Coefficient: <0.02% signal/mbar

Pressure Transient (60 cm H₂O step change): <150% signal change

Operating Humidity Range: 15%rH to 90%rH non-condensing

LIFETIME

Long Term Sensitivity Drift: <5% signal loss over operating life



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Expected Operating Life: 7 years in air

Life expectancy	> 7 anni
Range di misura	0-25% Ossigeno
Target Gas	Ossigeno
Tempo di Risposta	< 15 secondi (T90)
Uscita	80 - 130 μ A in air