

No image
available

7EF

Codice prodotto: 7EF

Produttore: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-10000 ppm CO

Maximum Overload: 2000 ppm CO

Filter: To remove SO_x/NO_x and H₂S

Sensitivity: 0.10 ± 0.02 µA/ppm

Response Time (T90)

- 7E: <25 seconds at 20°C
- 7E/F: <30 seconds at 20°C

Baseline Offset (clean air): -1 to +3 ppm equivalent

Zero Shift (+20°C to +40°C): <9 ppm equivalent

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: Not Required

MECHANICAL

Weight: 17 g nominal

Housing Material:

- Cap: Polycarbonate
- Body: ABS

Orientation: Any

ENVIRONMENTAL

Typical Applications: Portable Life Safety

Operating Temperature Range: -20°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric ± 10%

Pressure Coefficient: 0.020 ± 0.008 % signal/mBar

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: < 5% signal loss/year

Expected Operating Life: Three years in air

Storage Life: 6 months in CTL container

Life expectancy	> 3 anni
Range di misura	0-1000 ppm
Target Gas	Monossido di Carbonio
Tempo di Risposta	< 30 secondi (T90)
Uscita	100 ± 20 nA/ppm