

No image
available

7HH

Codice prodotto: 7HH

Produttore: City Technology

MEASUREMENT

Operating Principle: 3-electrode electrochemical

Measurement Range: 0-50 ppm H₂S

Maximum Overload: 500 ppm H₂S

Filter: None

Sensitivity: $1.7 \pm 0.3 \mu\text{A/ppm}$

Response Time (T90): <30 Seconds at 20°C

Baseline Offset (clean air): -0.2 to +0.4 ppm H₂S equivalent

Zero Shift (+20°C to +40°C): < 0.1 ppm H₂S equivalent

Resolution: 0.1 ppm (when used with recommended electronics)

Repeatability: 1% of signal

Linearity: Linear

ELECTRICAL

Recommended Load Resistor: 10 Ω

Bias Voltage: Not Required

MECHANICAL

Weight: 12 g nominal

Housing Material:

- Cap: Polycarbonate
- Body: ABS

Orientation: Any

ENVIRONMENTAL

Operating Temperature Range: -40°C to +50°C

Recommended Storage Temp: 0°C to 20°C

Operating Pressure Range: Atmospheric \pm 10%

Operating Humidity Range: 15 - 90% RH non-condensing

LIFETIME

Long Term Sensitivity Drift: < 2% signal loss/year
Expected Operating Life: Two years in air
Storage Life: 6 months in CTL container

Life expectancy	> 24 mesi
Range di misura	0-50 ppm
Target Gas	Acido Solfidrico
Tempo di Risposta	< 30 secondi (T90)
Uscita	1.7 ± 0.3 µA/ppm