



GUVx-T1xGS4

Codice prodotto: GUVx-T1xGS4

Produttore: Genicom Co., Ltd.

Description: UV Radiometer 4 is 3 Channel indicator. There are 3 type display, and 2 type output (Relay and 4-20 mA). 3 type display is the Relative Power (%), Accumulative Time (Hours), and Absolute Power (mW/cm²).

Costitution: Display, Sensor Probe 3 ea, Connection Cable 3 ea (5 m).

Application by UV Probe

- Air/Curing: LA2, LA5, LA6
- Water treatment: LW5, LW10

Features

- Fixing method: Panel Insertion
- Power: AC 200 ~ 240V (50/60Hz)
- Display:
 - Relative Power (%)
 - Accumulative Time (Hours)
 - Absolute Optical Power (mW/cm²)
 - 3 Color LED (Green, Yellow, Red)
- Output:
 - 4-20 mA Current, 5 V (Depends on Absolute Optical Power)
 - Relay

Specifications

- Size : 96 mm X 96 mm X 111 mm
- Operating Temperature:
 - Display : 0 ~ 50 C
 - UV Sensor Probe: -30 ~ 85 C
 - Cable length: 5m (Standard)
- Detection Range:
 - UVV : 230 ~ 395 nm
 - UVA : 220 ~ 370 nm
 - UVB : 220 ~ 320 nm
 - UVC : 220 ~ 280 nm



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Alimentazione	AC 200 ~ 240V 50/60 Hz
Dimensioni	96 x 96 x 111
Lunghezza d'onda	230-395 nm 220-370 nm 220-280 nm 220-320 nm
Uscita	4-20 mA Relè