



## GUVx-T1xGS6

**Codice prodotto:** GUVx-T1xGS6

**Produttore:** Genicom Co., Ltd.

**Description:** UV Radiometer 6 have 2 type display (Relative Power and Accumulative Time), and relay output, Simple to handle.

### Application by UV Probe

- Air/Curing: LA2
- Water treatment: LW9, LW10

### Features

- Fixing method: Panel Insertion
- Power: AC 85 ~ 265V (50/60Hz)
- Display:
  - Relative Power (unit : %)
  - Accumulative Time (unit : Hrs)
- Output:
  - Relay (NO&COM, 250VAC 3A/30VDC 3A)
  - 4-20 mA Current

### Specifications

- Size: 48 mm X 48 mm X 107 mm
- Operating Temperature:
  - Display: 0 ~ 50 C
  - UV Sensor Probe: -30 ~ 85 C
  - Probe cable length: 5 m (standard)
- Detection Range:
  - UVV : 230 ~ 395 nm
  - UVB : 220 ~ 320 nm
  - UVC : 220 ~ 280 nm

<b>Alimentazione</b>	AC 85 ~ 265V 50/60 Hz
<b>Dimensioni</b>	48 x 48 x 107
<b>Lunghezza d'onda</b>	220-280 nm 220-320 nm 230-395 nm



**Tecnosens S.p.A.**  
Via Vergnano,16 25125  
Brescia (BS) Italia  
  
Tel: (+39) 030 3534144  
Fax: (+39) 030 3530815  
info@tecnosens.it  
PEC: tecnosens@legalmail.it

Uscita

4-20 mA  
Relè