

# UV Radiometer 4

## GUVx-T1xGS4-LA5



### Description

UV Radiometer 4 is 3 Channel indicator. There are 3 type display, and 2 type output (Relay and 4-20 mA).  
3 type display is the absolute power, relative power, and accumulative time.

### Constitution

Display, Sensor Probe 3 ea, Connection Cable 3 ea (5 m)



### Sensor Probe Dimensions

Size (W×L×H, mm <sup>3</sup> )	Window (mm)	Weight (g)	Case Material	Cable Length (m)
36 × 30 × 16 mm <sup>3</sup>	12mm	40	AL-60	5

### Radiometer4 Dimensions

Size (W×L×H, mm <sup>3</sup> )	Window (mm)	Weight (g)	Case Material	Cable Length (m)
96 X 96 X 111	-	410	ABS	-

\* Panel Cutting Size : 92 × 92 mm<sup>2</sup> (Tolerance : -0, + 0.5 mm )

### Absolute Maximum Ratings

Parameter	Value			Unit	Remark
	Min.	Typ.	Max.		
Operating Temperature	-30		85	°C	Sensor Probe
	0		50	°C	Display
Working humidity	35		85	%RH	
Power Supply	200		240	VAC	50/60 Hz

### Electro-Optical Characteristics (at 25 °C)

Parameter	Value			Unit	Remark
	Min.	Typ.	Max.		
Detection Power Range	0		100	mW/cm <sup>2</sup>	
Detection Range	GUVV-T10GS4-LA5	230	395	nm	10% of Max
	GUVB-T11GS4-LA5	220	320	nm	
	GUVC-T10GS4-LA5	220	280	nm	
	GVBL-T12GS4-LA5	330	445	nm	

### Function

- Display : Relative Power (%), Accumulative Time (Hours), and Absolute Power (mW/cm<sup>2</sup>)  
3 Color LED : Green LED (Over C-03), Yellow LED(C-04 ~ C-03), Red LED (Under C-04)
- Output : DC Current (4-20 mA, 300 Ω max load), Relay (NC/NO, 250VAC 3A/30VDC 3A)